# 证明

## **CERTIFICATE**

67150016

本证明之附件是向中国专利局作为受理局提交的下列国际申请副本
THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY OF THE
BELOW

IDENTIFIED INTERNATIONAL APPLICATION THAT WAS FILED WITH THE CHINESE PATENT OFFICE AS RECEIVING OFFICE

国际申请号:

PCT/CN03/00339

INTERNATIONAL APPLICATION NUMBER

国际申请日:

12 MAY 2003(12.05.03)

INTERNATILNAL FILING DATE

发明名称:

SYSTEM AND METHOD FOR EDGE BLENDING

TITLE OF INVENTION

HARD DRIVE HEAD SLIDERS





中华人民共和国国家知识产权局局长
COMMISSIONER OF THE STATE INTELLECTUAL PROPERTY
OFFECE OF THE PEOPLE'S REPUBLIC OF CHINA

主意川

二零零三年七月十五日

JULY 15, 2003

# **PCT**

## **REQUEST**

The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty.

For receiving Office use only  PUT/CN 03/ 0 03 3 9  International Application No.					
Internation	12	MAY	2003	<b>(1 2.</b> 0 5. 0	3)
R	0/	CN <sub>P</sub>	中华人民 CT Inte	共和国国家知识产权 mational Applicat	局 ion

Applicant's or agent's file reference (if desired) (12 characters maximum) FPEL03150016

Name of receiving Office and "PCT International Application"

	(if desired) (12 charact	ers maximum) FPEL03150016	
Box No. 1 TITLE OF INVENTION SYSTEM AND METHOD FOR EDGE BLENDING	G HARD DRIVE I	HEAD SLIDERS	
Box No. 11 APPLICANT This person	is also inventor		
Name and address: (Family name followed by given name; for a legal entit The address must include postal code and name of country. The country of the Box is the applicant's State (that is, country) of residence if no State of residence	e address indicated in this	Telephone No.	
SAE MAGNETICS (H. K. ) LTD. SAE Tower,	·	Facsimile No.	
38-42 Kwai Fung Crescent		Teleprinter No.	
Kwai Chung N. T.			
Hong Kong Special Administrative Region, P. R. of China		Applicant's registration No. with the Office	
State (that is, country) of nationality:  CN	State (that is, country) CN	of residence:	
		the United States of America only the States indicated in the Supplemental Box	
Box No. III FURTHER APPLICANT(S) AND/OR (FURTH	ER) INVENTOR(S)		
Name and address: (Family name followed by given name; for a legal entir, The address must include postal code and name of country. The country of the Box is the applicant's State (that is, country) of residence if no State of residence ZHAN, Zhujian WINNERWAY INDUSTRIAL AREA, NANCHENG, DONGGUAN CITY, GUANGDONG PROVINCE, P.R. CHINA Zip Code: 511700	e address indicated in this	This person is:  applicant only  applicant and inventor  inventor only (If this check-box is marked, do not fill in below.)  Applicant's registration No. with the Office	
State (that is, country) of nationality:	State (that is, country)	of residence:	
This person is applicant all designated all designated for the purposes of:	States except tes of America	the United States the States indicated in the Supplemental Box	
Further applicants and/or (further) inventors are indicated on	a continuation sheet.		
Box No. IV AGENT OR COMMON REPRESENTATIVE;	OR ADDRESS FOR	CORRESPONDENCE	
The person identified below is hereby/has been appointed to act on of the applicant(s) before the competent International Authorities a	behalf s:	agent common representative	
Name and address: (Family name followed by given name; for a legal entity, The address must include postal code and name of cou	Telephone No. (852)28284688		
CHINA PATENT AGENT (H.K.) LTD. 22/F, Great Eagle Centre	Facsimile No. (852)28271018		
23 Harbour Road, Wanchai Hong Kong Special Administrative Region	Teleprinter No.		
The People's Republic of China	Agent's registration No. with the Office		
Address for correspondence: Mark this check-box where no	agent or common rans	ecentative is/has been appointed and the	
space above is used instead to indicate a special address to w	hich correspondence sh	ould be sent.	

Sheet No2	· · · · · · · · · · · · · · · · · · ·
Continuation of Box No. III FURTHER APPLICANT(S) AND/OR (FURTHER)	INVENTOR(S)
If none of the following sub-boxes is used, this sheet should not be included in the re	quest.
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)  FUJII, Ryuji  c/o SAE Magnetics (H.K.) Ltd.  SAE Tower 38-42, Kwai Fung Crescent  Kwai Chung, N. T.  Hong Kong Special Administrative Region	This person is:  applicant only  applicant and inventor  inventor only (If this check-hox is marked, do not fill in helow.)  Applicant's registration No. with the Office
P. R. of China	Approduct of the second
State (that is, country) of nationality:  State (that is, country)	) of residence:
This person is applicant all designated all designated States except the United States of America	the United States of America only the Supplemental Box
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)  WANG, Quanbao  WINNERWAY INDUSTRIAL AREA,  NANCHENG, DONGGUAN CITY,  GUANGDONG PROVINCE,	This person is:  applicant only applicant and inventor inventor only (If this check-box is marked, do not fill in below.)  Applicant's registration No. with the Office
P.R. CHINA Zip Code: 511700	
State (that is, country) of nationality:  State (that is, country)	of residence:
	the United States the States indicated in the Supplemental Box
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)  MAHADEV, Niraj  c/o SAE Magnetics (H.K.) Ltd.  SAE Tower 38-42, Kwai Fung Crescent  Kwai Chung, N. T.  Hong Kong Special Administrative Region  P. R. of China	This person is:  applicant only  applicant and inventor  inventor only (If this check-box is marked, do not fill in helow.)  Applicant's registration No. with the Office
State (that is, country) of nationality:  State (that is, country)	of residence:
	the United States the States indicated in the Supplemental Box
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)  YASUDA, Charlie c/o SAE Magnetics (H.K.) Ltd. SAE Tower 38-42, Kwai Fung Crescent Kwai Chung, N. T. Hong Kong Special Administrative Region P. R. of China  State (that is, country) of nationality:	This person is:  applicant only  applicant and inventor  inventor only (If this check-box is marked, do not fill in below.)  Applicant's registration No. with the Office  of residence:
	he United States the States indicated in the Supplemental Box
Further applicants and/or (further) inventors are indicated on another continuation s	heet.

Sheet	No.		.3	

Box No.	V DESIGNATION OF STATES	Mark the applicable check-hoxes below,	; at least one must be marked.			
	owing designations are hereby made tale all Patent	inder Rule 4.9(a):				
C AP	ADIDO DALES CH Chang Ci	M Gambia, KE Kenya, LS Lesotho, MW	Malawi, MZ Mozambique, SD Sudan,			
	SL Sierra Leone, SZ Swaziland, TZ State which is a Contracting State	of the Harare Protocol and of the PCT (if of	ther kind of protection or treatment desired,			
	specify on dotted line)  Lerasian Patent: AM Armenia, AZ Azerbaijan, BY Belarus, KG Kyrgyzstan, KZ Kazakhstan, MD Republic of Moldova, RU Russian Federation, TJ Tajikistan, TM Turkmenistan, and any other State which is a Contracting State of the Eurasian Patent Convention and of the PCT					
	- DCD-1 CU & I Switzerland and Liechtenstein CV Cynrus CZ Czech					
any other State which is a Contracting State of the European Fatent Convention and of the Policy of the European Fatent Convention and of the Policy of Contracting State of the European Fatent Convention and of the Policy of Contracting State of Indiana, CM Cameroon, GA Gabon, GN Guinea, GQ Equatorial Guinea, GW Guinea-Bissau, ML Mali, MR Mauritania, NE Niger, SN Senegal, TD Chad, TG Togo, and any other State which is a member State of OAPI and a Contracting State of the PCT (if other kind of protection or treatment desired, specify on dotted line)						
Nation	al Patent (if other kind of protection	or treatment desired, specify on dotted line):	□ NZ N Zeelend			
$\square$ AE	United Arab Emirates	☐ GM Gambia ☐ HR Croatia	□ NZ New Zealand			
☐ AG	Antigua and Barbuda	HU Hungary	PH Philippines			
L AL	Albania	D ID Indonesia	☐ PL Poland			
∐ AM □ AT	Ameria	L Israel	PT Portugal			
	Australia	□ IN India	☐ RO Romania			
□ A7.	Azerhaijan	☐ IS Iceland	LI RU Russian rederation			
□ BA	Bosnia and Herzegovina	☐ JP Japan				
□ вв	Barbados	KE Kenya	□ SD Sudan			
☐ BG	Bulgaria	☐ KG Kyrgyzstan	SE Sweden			
☐ BR	Brazil	KP Democratic People's Republic	☐ SG Singapore ☐ S1 Slovenia			
□ ву	Belarus	of Korea	SK Slovakia			
		KR Republic of Korea	☐ SL Sierra Leone			
☐ CA	Canada & LI Switzerland and Liechtenstein		☐ TJ Tajikistan			
M CN	China	LK Sri Lanka	☐ TM Turkmenistan			
	Colombia	☐ LR Liberia	☐ TN Tunisia			
☐ CR	Costa Rica	LS Lesotho	TR Turkey			
□ cu	Cuba	LT Lithuania	TT Trinidad and Tobago			
□ cz	Czech Republic	☐ LU Luxembourg	The second secon			
☐ DE	Germany	LV Latvia	TZ United Republic of Tanzania			
□ DK	Denmark	MA Morocco	UA Ukraine			
	I Dominica		☐ UG Uganda ☐ US United States of America			
∐ DZ	Algeria		Us officer states of America			
LEC	Ecuador	MK The former Vugoslav Republic of	UZ Uzbekistan			
HEE	Spain	Macedonia	□ VN Viet Nam			
LES	Finland	MN Mongolia	☐ YU Yugoslavia			
	United Kingdom	MWMalawi	ZA South Africa			
□ cn	Grenada	MX Mexico	☐ ZM Zambia			
□GE	Georgia		ZW Zimbabwe			
□ Сн	Ghana	□ NO Norway				
G11.	have below received for designating	States which have become party to the PCT	after issuance of this sheet:			
			. 🔲			
			. 🗖			
		addition to the designations made above, th	e applicant also makes under Rule 4.9(b) all			
Precautionary Designation Statement: In addition to the designations made above, the applicant also makes under Rule 4.9(b) all other designations which would be permitted under the PCT except any designation(s) indicated in the Supplemental Box as being excluded from the scope of this statement. The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit. (Confirmation (including fees) must reach the receiving Office within the 15-month time limit.)						

		S	Sheet No4			
`Box	No. VI PRIORITY	CLAIM				
The	priority of the following	earlier application(s) is here	by claimed:			
	Filing date Number Where earlier application is:					
(	of earlier application (day/month/year)	of earlier application	national application: country or Member of WTO	regional application:* regional Office	international application: receiving Office	
iten	1 (1)					
iten	1 (2)					
iten	1 (3)					
iten						
iten	1(5)					
	Further priority claims a	are indicated in the Suppleme	ental Box.			
if th	receiving Office is reque e earlier application was j	ested to prepare and transmit filed with the Office which for	to the International Bureau the purposes of this interna	a certified copy of the etional application is the r	receiving Office) identified	
	all items item (	1) item (2)	item (3) item	(4)	other, see Supplemental Box	
* W Inch	here the earlier application strial Property or one Me	on is an ARIPO application, ir ember of the World Trade Or	ndicate at least one country ganization for which that e	party to the Paris Conve earlier application was fit	ention for the Protection of led (Rule 4.10(b)(ii)):	
Box	No. VII INTERNAT	IONAL SEARCHING AUT	THORITY			
Cho	ice of International Sea national search, indicate	rching Authority (ISA) (if t the Authority chosen; the two	wo or more International S -letter code may he used):	earching Authorities are	competent to carry out the	
ISA	. / . CN					
	uest to use results of ear	rlier search; reference to the prity):	hat search (if an earlier se	earch has been carried ou	it by or requested from the	
Date	(day/month/year)	Numb	er Coun	try (or regional Office)		
Box	No. VIII DECLARAT	TIONS				
		are contained in Boxes Nos. te in the right column the nun			Number of declarations	
	Box No. VIII (i)	Declaration as to the identit	y of the inventor	•	:	
	Box No. VIII (ii)	Declaration as to the applic date, to apply for and be gr		international filing	:	
	Box No. VIII (iii)	Declaration as to the appli date, to claim the priority		e international filing	:	
	Box No. VIII (iv)	Declaration of inventorship United States of America)	o (only for the purposes of	the designation of the	:	
$\Box$	Box No. VIII (v)	Declaration as to non-preju	dicial disclosures or excep	otions to lack of novelty	:	

Sheet No. ...5...

Box No. IX CHECK LIST; LANGUAGE	OF FILING			
This international application contains:  (a) the following number of sheets in paper form:	This international application is accompanied by the following item(s) (mark the applicable check-boxes below and indicate in right column the number of each item):	Number of items		
request (including	1. The fee calculation sheet	: ' : 1		
declaration sheets) : 5 description (excluding	2. Soriginal separate power of attorney	. '		
sequence listing part) : 6	3. original general power of attorney			
claims : 5	4. copy of general power of attorney; reference number, if any:	. <b>:</b>		
abstract : 1	5. Statement explaining lack of signature	:		
drawings : 10	6. priority document(s) identified in Box No. VI as			
Sub-total number of sheets.	item(s):	:		
sequence listing part of description (actual number of sheets if filed in paper	7. translation of international application into (language):	:		
form, whether or not also filed in computer readable form; see (b) below)	8. separate indications concerning deposited microorganism or other biological material	:		
Total number of sheets : 27	9. sequence listing in computer readable form (indicate also type and number of carriers (diskette, CD-ROM, CD-R or other ))			
(b) sequence listing part of description filed in computer readable form	<ul> <li>(i) copy submitted for the purposes of international searce under Rule 13ter only (and not as part of the international application)</li> </ul>	h		
(i) only (under Section 801(a)(i))	(ii) \(\sum \) (only where check-box (b)(i) or (b)(ii) is marked in lej	9		
(ii) ☐ in addition to being filed in paper form (under Section 801(a)(ii))	column) additional copies including, where applicable the copy for the purposes of international search unde	e,		
Type and number of carriers (diskette, CD-ROM, CD-R or other) on which the	Rule 13 <i>ter</i> (iii) together with relevant statement as to the identity	:		
sequence listing part is contained (additional	of the copy or copies with the sequence listing part			
copies to be indicated under item 9(ii), in right column):	mentioned in left column	:		
	10. other (specify):	<u> </u>		
Figure of the drawings which should accompany the abstract: FIG. 8	Language of filing of the international application: EN	_		
Box No. X SIGNATURE OF APPLICANT, AGENT OR COMMON REPRESENTATIVE  Next to each signature, indicate the name of the person signing and the capacity in which the person signs (if such capacity is not obvious from reading the request).  TOTAL PROPERTY OF APPLICANT, AGENT OR COMMON REPRESENTATIVE  Next to each signature, indicate the name of the person signing and the capacity in which the person signs (if such capacity is not obvious from reading the request).				
	For receiving Office use only			
Date of actual receipt of the purported international application:	1 2 MAY 2003 (1 2. 0 5. 0 3)	Orawings: received:		
Corrected date of actual receipt due to later timely received papers or drawings completi the purported international application:				
4. Date of timely receipt of the required corrections under PCT Article 11(2):		not received:		
International Searching Authority     (if two or more are competent): ISA /	6. Transmittal of search copy delayed until search fee is paid			
For International Bureau use only				
Date of receipt of the record copy by the International Bureau:				

This sheet is not part of and does not count as a sheet of the international application.

# FEE CALCULATION SHEET

For receiving Office use only	
PCT/CN 03/ 0 03 3 9 mational Application No.	

Annex to the Request		- Hernaudiar Application 140.			
Applicant's or agent's file reference	FPEL03150016	1 2 MAY 2003 (1 2. 0 5	1 2 MAY 2003 (1 2. 0 5. 0 3) e stamp of the receiving Office		
Applicant					
SAE MAGNETICS	(H.K.) LTD.				
CALCULATION OF PRES	CRIBED FEES		./~		
1. TRANSMITTAL FEE .		CNY500 T	V 500,-		
2. SEARCH FEE	carried out by  I Searching Authorities are competent to carry of the Authority which is chosen to carry out the in	ut the international atternational search.)	<u> </u>		
3. INTERNATIONAL FEE Basic Fee	·				
	o. IX applies, enter Sub-total number of so. IX does not apply, enter Total number	of sheets }	41-650x		
b1 first 30 sheets	<u> </u>	CHF650 [b1]C	71-130		
number of shee	ts fee per sheet	<u>b2</u> ,			
b3 additional componer is filed in computer	, nt (only if sequence listing part of descrip readable form under Section 801(a)(i), or d on paper, under Section 801(a)(ii)):	tion			
•	400 x =	b3			
Add amounts entered at b	fee per sheet 1, b2 and b3 and enter total at B		F650,		
Designation Fees The international applicat	ion contains1_ designations.	·			
1	xCHF140 =	CHF140 D CH	F140,-		
number of designation fe payable (maximum 5)	es amount of designation fee	CHF790 []	, T 7982		
	and D and enter total at I	· · · · · <del></del>	7F > 10x		
(Applicants from certain international fee. Where the to be entered at 1 is 25% of	States are entitled to a reduction of 75% applicant is (or all applicants are) so entitled the sum of the amounts entered at B and D	% of the l, the total			
4. FEE FOR PRIORITY DO	CUMENT (if applicable)	.,	NY2000,-		
5. TOTAL FEES PAYABLE	·	CNY2000CHF790	HF 790,		
Add amounts entered at T	S, I and P, and enter total in the TOTAL b	50X			
The designation fees are	e not paid at this time.		*		
MODE OF PAYMENT					
authorization to charge deposit account (see belo	w) postal money order	cash coupons			
Cheque	bank draft	revenue stamps other (specify):			
AUTHORIZATION TO CHARGE (OR CREDIT) DEPOSIT ACCOUNT (This mode of payment may not be available at all receiving Offices)  Receiving Office: RO/					
Authorization to charge	the total fees indicated above.	Deposit Account 10			
(This check-box may be m of the receiving Office so p	arked only if the conditions for deposit accou vermit) Authorization to charge any deficien nt in the total fees indicated above.				
	the fee for priority document.	Signature:			
Co DCT/DO/101 (A) (I	anuary 2002: reprint July 2002)	* 3//	calculation sheet		

15

20

25

## SYSTEM AND METHOD FOR EDGE BLENDING HARD DRIVE HEAD SLIDERS

1

## **Background Information**

5 [0001] The present invention relates to hard disk drives. More specifically, the invention relates to a system and method for edge blending hard drive head sliders.

[0002] Figure 1 provides an illustration of a typical hard disk drive. Hard disk drive storage devices typically include a rotating disk 1 mounted for rotation by a spindle motor (not shown). A slider 3, supported by a suspension arm 5, 'flies' over the surface of the magnetic disk 1 at a high velocity, reading data from and writing data to concentric data tracks 11 on the disk 1. The slider 1 is positioned radially by a voice coil motor 7.

[0003] Figure 2 shows a more detailed view of a head slider 3 flying over the surface of a magnetic disk 1 as is typical in the art. Modern head sliders 3 float over the surface of the disk 1 on a cushion of air. If the 'flying height' is too great, the head 12 on the head slider cannot properly read from and write to the disk 1. If it is too small, there is an increased chance of a head crash.

[0004] If a head slider 3 contacts the surface of the disk while it is at operational speed, the result can be a loss of data, damage to the head slider, damage to the surface of the disk 1, or all three. One of the most common causes of head crashes is a contaminant getting wedged in the microscopic gap between head 3 and disk 1. Head sliders 3 are typically ceramic for durability and corrosion resistance. A ceramic slider is durable due to its hardness. The tradeoff, however, of ceramic's hardness is its brittleness. When a row bar is cut into individual sliders 3 (explained below), the ceramic crystal array causes the slider 3 edges to crack easily. Loose chips of ceramic material may be found on the cutting surface edge corners even after solvent cleaning. Also, after cutting a row bar into individual sliders, a high point is often left on the cut slider surface. This is known as 'edge jump'. Edge jump is believed to be from the stress applied to the cut edge of the slider 3. A deformation layer is created by the

r ÁAlic.

pressure 20 created by the cutting process. (See Figure 3).

10

[0005] Figure 3 illustrates the problems related to particle contamination and edge jump as is typical in the art. The problems concerning loose chips 21 and edge jump 20 can cause hard drive head crashes. A loose chip 21 may fall from the slider and contaminate the interface between the slider 3 and disk 1. An edge jump 20 can affect a slider's anti-shock performance negatively. If the HDD gets a physical impact while operating, a location of edge jump may contact and damage the disk 1.

[0006] It is therefore desirable to have a system and method for edge blending hard

drive head sliders, that avoids the above-mentioned problems, as well as having additional benefits.

## Brief Description Of The Drawings

20

[0007] Figure 1 provides an illustration of a typical hard disk drive.

[0008] Figure 2 shows a more detailed view of a head slider flying over the surface of a magnetic disk as is typical in the art.

[0009] Figure 3 illustrates the problems related to particle contamination and edge jump as is typical in the art.

[0010] Figure 4 illustrates a head parting jig as is typical in the art.

[0011] Figure 5 illustrates an edge blending jig according to an embodiment of the present invention.

10 [0012] Figure 6 illustrates the attachment of a head blending jig to a head blending machine according to an embodiment of the present invention.

[0013] Figure 7 illustrates portions of lapping tape inserted between individual head sliders mounted to an edge blending jig in a standby configuration and in two edge blending configurations according to an embodiment of the present invention.

15 [0014] Figure 8 provides a more detailed illustration of lapping tape partially wrapping a slider's edge to perform edge blending according to an embodiment of the present invention.

[0015] Figure 9 provides a detailed view of an individual slider mounted to an arm of an edge blending jig with lapping tape partially wrapping a slider edge for edge blending according to an embodiment of the present invention.

[0016] Figure 10 illustrates an edge blending machine according to an embodiment of the present invention.

10

15

20

25

[0017] Figure 4 illustrates head parting jig as is typical in the art. As is illustrated in figure 4a, a slider row bar 401 is typically bonded to multiple arms 402 of a head parting jig 403. As is illustrated in figure 4b and described further below, the row bar is cut into individual head sliders 3 by a slider parting tool (not shown).

[0018] Figure 5 illustrates an edge blending jig according to an embodiment of the present invention. As illustrated in Figure 5a, in one embodiment, a slider row bar 501 is bonded to multiple arms 502 of the edge blending jig, whereupon the row bar is separated into individual head sliders 3 by a slider parting tool (not shown). One advantage of this jig design is that imperfections on the edges of the sliders 3 (such as edge jump) can be detected by viewing the sliders from behind 505 and observing the uniformity of gaps between the sliders 3.

[0019] Figure 6 illustrates the attachment of a head blending jig to a head blending machine according to an embodiment of the present invention. In one embodiment, the edge blending jig is coupled to a support assembly 12 of the head blending machine by a pair of pins 11.

[0020] Figure 7 illustrates portions of lapping tape inserted between individual head sliders mounted to an edge blending jig in a 'standby' configuration and in two edge blending configurations according to an embodiment of the present invention. As illustrated in figure 7a, in one embodiment, lapping tape 701 covered with an abrasive, such as diamond powder (e.g., of a grade between 0.1 microns and 3.0 microns), is inserted between sliders 3. Figure 7a shows the edge blending assembly in a 'standby' configuration with the sliders 3 out of contact with the lapping tape 701. Figure 7b shows the edge blending assembly configured to partially wrap the lapping tape 701 across one of the edges of each slider 3 on the edge blending jig 2 according to an embodiment of the present invention. In this embodiment, the lapping tape is positioned by an adjustable series of rollers (described below) to be stretched across the slider edges at a predetermined tension force (e.g., less than 0.8 kilograms). In this embodiment, the edge blending jig 2 is directionally oscillated 712 by the edge

- 13

blending assembly to cause relative motion between the sliders 3 and the lapping tape 701 (e.g., at a frequency of at least 1 cycle per second and at an amplitude between 10 millimeters and 40 millimeters). Figure 7c shows the edge blending assembly configured to partially wrap the lapping tape 701 across the opposite edge of each slider 3 according to an embodiment of the present invention. In this embodiment, the edge blending assembly is configured to stretch the lapping tape 701 across the opposite edge of each slider to complete the edge blending process. As explained below, in one embodiment, the process of edge blending is performed submerged in lubricant.

5

10

15

20

[0021] Figure 8 provides a more detailed illustration of lapping tape partially wrapping a slider's edge to perform edge blending according to an embodiment of the present invention. In one embodiment, a first angle ( $\alpha$ ) is formed between a face 805 of the slider 3 and the lapping tape 801, and a second angle ( $\beta$ ) is formed between the opposite face 806 of the slider 3 and the lapping tape 801 ( $\alpha$ . and  $\beta$  being between 3 degrees and 90 degrees, for example).

[0022] Figure 9 provides a detailed view of an individual slider mounted to an arm of an edge blending jig with lapping tape partially wrapping a slider edge for edge blending according to an embodiment of the present invention. In one embodiment, after a row bar is bonded to multiple arms of an edge blending jig 2 (by, e.g., epoxy) and cut into individual mounted sliders 3 (such as by a diamond cutting wheel), lapping tape 1 is inserted between the sliders 3 and the edge blending assembly is configured to wrap the lapping tape 1 around an edge of the slider 3 under a predetermined amount of tensile force. As stated above, in this embodiment, the slider 3 is directionally oscillated to achieve relative motion between the slider 3 and the lapping tape 1.

[0023] Figure 10 illustrates an edge blending machine according to an embodiment of the present invention. In one embodiment, an edge blending jig with mounted sliders is coupled to a jig support 5 and mounted in the edge blending machine. In this embodiment, a top platform 4, containing lapping tape rollers 16, is attached to a base unit 9, supporting the edge blending jig. In this embodiment, portions of lap tape 1001 are positioned and kept in alignment by a series of guide arms 17. In this embodiment

a spring mechanism 6, which is adjusted by a tension adjustment knob 1002, is utilized to maintain the appropriate tensile force for the portions of lapping tape 1001. Maintaining appropriate lapping tape tension is important to prevent lapping tape 1001 breakage or dislodging of sliders from the edge blending jig arms.

5

10

15

[0024] In this embodiment, another adjustment knob 1003 is utilized to move the lapping tape portions relative to the sliders (on the edge blending jig) to shift the relative position to partially wrap the slider edges appropriately (to provide the appropriate angles of  $\alpha$ . and  $\beta$ ). In this embodiment, the process of edge blending is performed with the edge blending assembly submerged in lubricant. In this embodiment, a reservoir 7 is filled above the level of the sliders with a lubricant (such as a mixture of de-ionized (DI) water and oil) before edge blending.

[0025] In one embodiment, rubber tape is used instead of the lapping tape with the reservoir 7 filled with a diamond slurry. In this embodiment, the diamond particles travel on the rubber tape as an abrasive to smooth the slider edge's surface. Also, in an embodiment, a cleaning process could be performed after edge blending, wherein the lapping tape 1001 is replaced with rubber tape and the reservoir 7 is filled with a cleaning solution. The slider would be oscillated with respect to the rubber tape in the cleaning solution to clean any debris left on the sliders after the edge blending process.

[0026] Although several embodiments are specifically illustrated and described herein, it will be appreciated that modifications and variations of the present invention are covered by the above teachings and within the purview of the appended claims without departing from the spirit and intended scope of the invention.

#### What is Claimed is

5

10

15

20

25

ĺ.

1. A system for manufacturing a hard disk drive head slider comprising:

an edge blending jig of an edge blending assembly to bond to a number of head sliders for edge blending, said edge blending by lapping tape, wherein

said edge blending jig is configured to receive a portion of lapping tape between each of a number of said sliders;

said edge blending jig is configured to allow said lapping tape to partially wrap an edge of each slider; and

said edge blending is performed by relative movement between said sliders and said lapping tape.

- 2. The system of claim 1, wherein said edge blending is by directional oscillation of said sliders with respect to said lapping tape.
- 3. The system of claim 2, wherein said oscillation of the sliders is at a frequency of at least 1 cycle per second.
- 4. The system of claim 2, wherein said oscillation of the sliders is at an amplitude of at least 10 millimeters.
  - 5. The system of claim 2, wherein said slider oscillation is performed with a first angle ( $\alpha$ ) between a first face of the slider and the lapping tape and with a second angle ( $\beta$ ) between a second face of the slider and the lapping tape, said first angle and said second angle each being between 3 degrees and 90 degrees.
- 6. The system of claim 2, wherein said slider oscillation is performed with a portion of lapping tape partially wrapped around an edge of each slider under a tension force of at least 0.05 kilograms.

- 7. The system of claim 2, wherein said edge blending is performed with said sliders and said lapping tape submerged in a lubricant.
- 8. The system of claim 2, wherein said lapping tape has a lapping surface covered with an inorganic powder.
- 9. The system of claim 8, wherein said inorganic powder is diamond powder.

20

- 10. The system of claim 8, wherein said powder has a grade between 0.1 microns and 3.0 microns.
  - 11. The system of claim 2, wherein said lapping tape has a thickness between 40 microns and 100 microns.
- 12. The system of claim 2, wherein said lapping tape is greater than 1.2 millimeters in width.
  - 13. The system of claim 2, wherein a slider row bar is to be bonded to said edge blending jig, said row bar to be separated into individual head sliders upon the edge blending jig.
  - 14. The system of claim 13, wherein said row bar is to be separated into individual sliders by a diamond cutting wheel.
- 15. The system of claim 2, wherein for a slider cleaning process said lapping tape is a rubber tape and said oscillation is performed with said sliders and said rubber tape submerged in a cleaning solution.
  - 16. The system of claim 15, wherein said cleaning process is performed for at least 30

seconds.

5

10

15

20

25

- 17. The system of claim 2, wherein said lapping tape is a rubber tape and said oscillation is performed with said sliders and said rubber tape submerged in a diamond slurry.
- 18. A method for manufacturing a hard disk drive head slider comprising:

inserting lapping tape between each of a number of head sliders bonded to a edge blending jig of an edge blending assembly;

adjusting said edge blending assembly to cause the lapping tape to partially wrap an edge of each slider; and

edge blending said head sliders by relative movement between said sliders and said lapping tape.

- 19. The method of claim 18, wherein said edge blending is by directional oscillation of said sliders with respect to said lapping tape.
  - 20. The method of claim 19, wherein said oscillation of the sliders is at a frequency of at least 1 cycle per second and an amplitude of at least 10 millimeters.
  - 21. The method of claim 19, wherein said slider oscillation is performed with a first angle ( $\alpha$ ) between a first face of the slider and the lapping tape and with a second angle ( $\beta$ ) between a second face of the slider and the lapping tape, said first angle and said second angle each being between 3 degrees and 90 degrees.

22. The method of claim 19, wherein said slider oscillation is performed with a portion of lapping tape partially wrapped around an edge of each slider under a tension force of at least 0.05 kilograms.

- 23. The method of claim 19, wherein said edge blending is performed with said sliders and said lapping tape submerged in a lubricant.
- 24. The method of claim 19, wherein said lapping tape has a lapping surface covered with a diamond powder having a grade between 0.1 microns and 3.0 microns.
- 25. The method of claim 19, wherein said lapping tape has a thickness between 40 microns and 100 microns.
- 26. The method of claim 19, further comprising:
  bonding a head slider row bar to said edge blending jig; and
  separating said row bar into said number of head sliders.

20


- 27. The method of claim 26, wherein said separating said row bar is performed by a slider parting tool.
  - 28. The method of claim 19, wherein for a slider cleaning process said lapping tape is a rubber tape and said oscillation is performed with said sliders and said rubber tape submerged in a cleaning solution.
  - 29. The method of claim 28, wherein said cleaning process is performed for at least 30 seconds.
- 30. The method of claim 19, wherein said lapping tape is a rubber tape and said oscillation is performed with said sliders and said rubber tape submerged in a diamond slurry.
  - 31. A method for manufacturing a hard disk drive head slider comprising:
    bonding a head slider row bar to a edge blending jig of an edge blending assembly;

separating upon the edge blending jig the row bar into a number of head sliders; inserting lapping tape between each slider on the edge blending jig; adjusting said edge blending assembly to cause the lapping tape to partially wrap an edge of each slider; and

edge blending said head sliders by motion oscillation of said sliders with respect to said lapping tape.

## Abstract

A system and method are disclosed for edge blending hard drive head sliders by oscillating abrasive lapping tape across the edges of multiple sliders simultaneously.







FIG.2 (Prior Art)


iaju Jaju






F1G. 3b


FIG.3 (Prior Art)





F1G. 3a



. . .







F1G. 7





FIG. 8





F1G. 9




FIG. 10